



ES-BSC Series NSF Certified Hoods

Class II A2



Display for NA series




Display for GL series

Color Touch Screen

Touch operation, real-time and clearer display of various values and appointment timing function.



Exhaust Thimble canopy (Optional)



Front Window

Two-layer laminated toughened glass >6mm, Anti UV



Footmaster Caster

Universal caster with brake and leveling feet.



Stainless Steel I.V. Bar with 10 hooks



SS Water Tap & Gas Tap




Waterproof Socket



Wind Speed Sensor



Work Zone Unibody design



UV Lamp

Emission of 253.7 nanometers for most efficient decontamination.

ADVANTAGE

1. Motorized front window.
2. 7-inch large touch color display: touch operation, real-time and clearer display of various values of the safety cabinet, dynamic air flow pattern diagram, fault alarm sound and light prompt.
3. The power-on password can be set to prevent mis-operation by irrelevant personnel.
2. EC Fan, automatically adjust the wind speed.
3. With power-off memory function, the state before power-off will be restored after power-on and there will be visual prompts and alarms.
4. The integrated design of the operation area makes it easy to disassemble and clean.
5. The cabinet is separated from the base. The height of the adjustable base can be customized.
6. Interlocking function: UV lamp and front window; UV lamp and fan; fan and front window.
7. It has the function of appointment timing, which can automatically set the time of starting and shutting down the safety cabinet and the running time of ultraviolet lamps, fan and sockets.
8. The front window closes the trigger signal, so that the sterilization and disinfection function of the ultraviolet lamp is normally turned on.
9. The one-piece hand resting surface has a larger contact area with the arm and is more comfortable. air speed adjustable with filter block.

Model		ES-BSC-4FA2	ES-BSC-3FA2GL	ES-BSC-4FA2GL	ES-BSC-6FA2GL
			ES-BSC-3FA2NA	ES-BSC-4FA2NA	ES-BSC-6FA2NA
External Size(W*D*H)		1383*775*2220mm	1087*775*2220mm	1383*775*2220mm	1873*775*2240mm
Internal Size(W*D*H)		1210*600*660mm	910*600*660mm	1210*600*660 mm	1700*600*660mm
Work Surface Height		762mm	762mm	762mm	782mm
Max Opening		470mm			
Tested Opening		Safety height 200mm (8")	Safety height 254mm (10")		
Airflow Volume	Inflow	462m ³ /h (272cfm)	445m ³ /h(259cfm)	587m ³ /h(346cfm)	824m ³ /h(485cfm)
	Downflow	65%: 863m ³ /h (507cfm)	60%: 649m ³ /h (382cfm)	60%: 863m ³ /h (507cfm)	60%: 1212m ³ /h(713cfm)
	Exhaust	35%: 462m ³ /h (272cfm)	40%:445m ³ /h (259cfm)	40%: 587m ³ /h (346cfm)	40%:824m ³ /h (485cfm)
Front Window		Motorized. Two-layer laminated toughened glass ≥6mm. Anti UV.			
ULPA Filter		Two, 99.9995% efficiency at 0.12μl, filter life Indicator.			
Filter Guard Type		Aluminum alloy frame, glass fiber filter paper			
Noise		NSF 49s67dB			
Illumination		≥1000Lux			
Display		Color Touch Screen			
Waterproof Socket		Two, Total consumption: ≤500W			
Tap		Water tap*1, Gas tap*1			
Ground Resistance		≤0.10Ω			
Power Supply		AC230V, 50/60Hz; AC115V, 60Hz, Full load Amps: 9A, BTU/Hr: 1689			
Consumption		500W	400W	500W	700W
Alarm		Abnormal airflow velocity; Filter replacement; Front window at unsafe height; High filter pressure alarm			
DC Motor		One ECM motor, 115V& 230V acceptable, Speed adjustable, high efficiency and low power consumption			
Material		Working area: 304 stainless steel			
		Frame and Decorative Plate: cold-rolled steel with anti-bacteria power coating			
UV Lamp		30W	20W	30W	40W
		Germicidal UV lamp, Emission of 253.7 nanometers for most efficient decontamination			
Illuminating Lamp		20W*2	10W*2	20W*2	23W*2
		LED lamp			
Standard Accessory		LED lamp*2, UV lamp*1, Base stand, SS water tap*1, SS gas tap*1, Drain valve			
		Waterproof sockets*2, Stainless Steel IV Bar with 10 hooks,Remote control			
Optional Accessory		Armrest, Airflow tester, Formalin fumigation sterilizer, Infrared sterilizer			
		Electric height adjustable base stand			
Package Size (W*D*H)		1540*1080*1900mm	1240*1060*1900mm	1540*1080*1900mm	2020*1080*1900mm
Gross Weight		330kg	280kg	330kg	410kg



ESSE3 srl, Via Garibaldi 30
14022 Castelnuovo D.B. (AT)
Tel +39 011 99 27 706
Fax +39 011 99 27 506
e-mail: danielec@esse3-medical.com
web: www.esse3-medical.com

